

■后备时间的参考标准（中国销售机型）■

※环境温度为20℃、电池为初始状态时。本后备时间表仅供参考。根据外部环境（温度等）不同，电池寿命也不同。

●后备式（BX/BY系列）

时间单位：（分钟）

型号 / 负载容量	20W	50W	100W	200W	300W	400W	600W	800W	1000W
BX50FCH	120	48	20	6	3.5	-	-	-	-
BX50FWCH	120	48	20	6	3.5	-	-	-	-
BX75SWCH	200	110	50	19	9	6	5(450W)	-	-
BY50SCH	90	40	15	6.5	3.5	-	-	-	-
BY120SCH	300	130	63	27	17.5	11	5.5	4(720W)	-
BY50FWCH	80	35	14	5.5	3.5	-	-	-	-
BY75SWCH	180	70	30	12	7	5.5	5(450W)	-	-

●在线互动式（BN系列）

时间单位：（分钟）

型号 / 负载容量	20W	50W	100W	200W	300W	400W	600W	800W	1000W	1200W	1400W	1600W	1800W	2000W	2300W	2700W
BN50T	250	110	55	24	15.5	10.5	8.5(450W)	-	-	-	-	-	-	-	-	-
BN75T	250	110	55	24	15.5	10.5	5.8	4(680W)	-	-	-	-	-	-	-	-
BN100T	480	215	120	56	35	25	16	11	9(900W)	-	-	-	-	-	-	-
BN150T	480	215	120	56	35	25	16	11	8	6.2	4.5(1350W)	-	-	-	-	-
BN220T	900	460	250	125	81.5	57	36	25	18	14	11	9.5	8	7(1980W)	-	-
BN300T	900	460	250	125	81.5	57	36	25	18	14	11	9.5	8	7	5.8	4.5
BN75R	250	100	55	24	15.5	10.5	5.8	4(680W)	-	-	-	-	-	-	-	-
BN150R	480	215	120	56	35	25	16	11	8	6.2	4.5(1350W)	-	-	-	-	-
BN300R	600	300	170	90	55	40	26	18	13	10.2	8.2	6.4	5	4.5	2.7	2.5

●在线式（BU系列）

时间单位：（分钟）

型号 / 负载容量	20W	50W	100W	200W	300W	400W	600W	800W	1000W	1200W	1400W	1600W	1800W	2000W	2300W	2700W	3000W	3300W	3500W
BA75T	200	109	56	23	14	9	6	-	-	-	-	-	-	-	-	-	-	-	-
BA100T	200	109	56	23	14	9	6	4	-	-	-	-	-	-	-	-	-	-	-
BA100R	200	109	56	23	14	9	6	4	-	-	-	-	-	-	-	-	-	-	-
BU75SWCH	120	75	40	20	12	7	5(500W)	-	-	-	-	-	-	-	-	-	-	-	-
BU150SWCH	210	150	70	37	23	17	10	7	4.2	4(1050W)	-	-	-	-	-	-	-	-	-
BU100RWCH	250	150	85	36	23	18	10	7	-	-	-	-	-	-	-	-	-	-	-
BU300RWCH	320	220	150	80	52	40	26	18	14	11	9	7	6	5.3	4.3	4(2400W)	-	-	-
BU100RECH	150	110	72	32	20	15	8.5	6	-	-	-	-	-	-	-	-	-	-	-
BU1002SWCL	180	120	60	35	20	15	7	5(700W)	-	-	-	-	-	-	-	-	-	-	-
BU3002SWCL	360	250	170	92	58	46	30	20	15	12	10	8	7	5.5	5(2100W)	-	-	-	-
BU1002SWCH	180	120	60	35	20	15	7	5(700W)	-	-	-	-	-	-	-	-	-	-	-
BU3002SWCH	360	250	170	92	58	46	30	20	15	12	10	8	7	5.5	5(2100W)	-	-	-	-
BU1002RW	140	80	48	24	15	11	6	3.5	-	-	-	-	-	-	-	-	-	-	-
BU2002RWL	360	190	110	60	39	27	16	12	9.5	7	5	-	-	-	-	-	-	-	-
BU3002RWL	450	260	165	93	63	45	28	19	15	11	9	7.5	6	5.2	5(2100W)	-	-	-	-
BU5002RWL	660	480	320	200	140	106	68	50	39	31	25	21	18	16	15(2100W)	10	8	7	5