

■ 后备时间的参考标准（中国销售机型）

※周围温度为20℃、电池初始状态时。本后备时间表仅供参考。根据外部环境（温度等）不同，电池寿命也不同。

● 后备式 (BZ/BX/BY系列)

时间单位：（分钟）

型号/负载容量	20W	50W	100W	200W	300W	400W	600W	800W	1000W
BX50FCH	120	48	20	6	3.5	-	-	-	-
BX50FWCH	120	48	20	6	3.5	-	-	-	-
BX75SWCH	200	110	50	19	9	6	5(450W)	-	-
BY50SCH	90	40	15	6.5	3.5	-	-	-	-
BY120SCH	300	130	63	27	17.5	11	5.5	4(720W)	-
BY50FWCH	80	35	14	5.5	3.5	-	-	-	-
BY75SWCH	180	70	30	12	7	5.5	5(450W)	-	-

● 在线互动式 (BN系列)

时间单位：（分钟）

型号/负载容量	20W	50W	100W	200W	300W	400W	600W	800W	1000W	1200W	1400W	1600W	1800W	2000W	2300W	2700W
BN75R	250	100	55	24	15.5	10.5	5.8	4(680W)	-	-	-	-	-	-	-	-
BN150R	480	215	120	56	35	25	16	11	8	6.2	4.5(1350W)	-	-	-	-	-
BN300R	600	300	170	90	55	40	26	18	13	10.2	8.2	6.4	5	4.5	2.7	2.5

● 在线式 (BU系列)

时间单位：（分钟）

型号/负载容量	20W	50W	100W	200W	300W	400W	600W	800W	1000W	1200W	1400W	1600W	1800W	2000W	2300W	2700W	3000W	3300W	3500W
BU75SWCH	120	75	40	20	12	7	5(500W)	-	-	-	-	-	-	-	-	-	-	-	-
BU150SWCH	210	150	70	37	23	17	10	7	4.2	4(1050W)	-	-	-	-	-	-	-	-	-
BU100RWCH	250	150	85	36	23	18	10	7	-	-	-	-	-	-	-	-	-	-	-
BU300RWCH	320	220	150	80	52	40	26	18	14	11	9	7	6	5.3	4.3	4(2400W)	-	-	-
BU1002SWCH	180	120	60	35	20	15	7	5(700W)	-	-	-	-	-	-	-	-	-	-	-
BU3002SWCH	360	250	170	92	58	46	30	20	15	12	10	8	7	5.5	5(2100W)	-	-	-	-
BU100RECH	150	110	72	32	20	15	8.5	6	-	-	-	-	-	-	-	-	-	-	-
BU1002RW	140	80	48	24	15	11	6	3.5	-	-	-	-	-	-	-	-	-	-	-
BU2002RWL	360	190	110	60	39	27	16	12	9.5	7	5	-	-	-	-	-	-	-	-
BU3002RWL	450	260	165	93	63	45	28	19	15	11	9	7.5	6	5.2	5(2100W)	-	-	-	-
BU5002RWL	660	480	320	200	140	106	68	50	39	31	25	21	18	16	15(2100W)	10	8	7	5

后备时间的参考标准（日本销售机型）

※周围温度为20℃、电池初始状态时。本后备时间表仅供参考。根据外部环境（温度等）不同，电池寿命也不同。

●后备式（BZ/BX/BY系列）

时间单位：（分钟）

型号/负载容量	20W	50W	100W	200W	300W	400W	600W	800W	1000W
BZ35LT2 (*1)	90	42	19	6	5(210W)	-	-	-	-
BZ50LT2 (*1)	90	42	19	6	3	-	-	-	-
BX35F	120	48	20	6	5(210W)	-	-	-	-
BX50F	120	48	20	6	3.5	-	-	-	-
BX50FW	120	48	20	6	3.5	-	-	-	-
BX75SW	200	110	50	19	9	6	5(450W)	-	-
BY35S	90	40	15	6.5	6(210W)	-	-	-	-
BY50S	90	40	15	6.5	3.5	-	-	-	-
BY80S	170	100	40	15	9	6	4(500W)	-	-
BY120S	300	130	63	27	17.5	11	5.5	4(720W)	-
BY50FW	80	35	14	5.5	3.5	-	-	-	-
BY75SW	180	70	30	12	7	5.5	5(450W)	-	-

(\*1)最大后备时间的限制。无法后备90分钟以上。

●在线互动式（BN系列）

时间单位：（分钟）

型号/负载容量	20W	50W	100W	200W	300W	400W	600W	800W	1000W	1200W	1400W	1600W	1800W	2000W	2300W	2700W
BN50S	230	109	49	21	12	8.2	5.5(450W)	-	-	-	-	-	-	-	-	-
BN75S	230	109	49	21	12	8.2	4.6	3.5(680W)	-	-	-	-	-	-	-	-
BN100S	620	290	140	60	35	24	13	9	7.9(900W)	-	-	-	-	-	-	-
BN150S	620	290	140	60	35	24	13	9	7	5.5	5(1350W)	-	-	-	-	-
BN220S	900	600	320	150	88	64	38	25	18	15	12	10	8.4	7(1980W)	-	-
BN300S	900	600	320	150	88	64	38	25	18	15	12	10	8.4	7.5	6	5
BN75R	250	100	55	24	15.5	10.5	5.8	4(680W)	-	-	-	-	-	-	-	-
BN150R	480	215	120	56	35	25	16	11	8	6.2	4.5(1350W)	-	-	-	-	-
BN300R	600	300	170	90	55	40	26	18	13	10.2	8.2	6.4	5	4.5	2.7	2.5
BN100XR	220	130	70	37	20	15	9	7(700W)	-	-	-	-	-	-	-	-
BN150XR	220	130	70	37	20	15	9	5.5	4	-	-	-	-	-	-	-
BN240XR	340	230	130	70	50	35	20	14	12	10	8	7	6	5	-	-
BN240XR+MR240XR×1	750	500	280	180	120	80	50	35	30	22	18	16	14	11	-	-
BN240XR+MR240XR×2	1200	800	500	240	180	120	80	60	50	40	34	29	22	20	-	-

●在线式（BU系列）

时间单位：（分钟）

型号/负载容量	20W	50W	100W	200W	300W	400W	600W	800W	1000W	1200W	1400W	1600W	1800W	2000W	2300W	2700W	3000W	3300W	3500W
BU50SW	120	75	40	20	12	8(350W)	-	-	-	-	-	-	-	-	-	-	-	-	-
BU75SW	180	75	40	20	12	7	5(500W)	-	-	-	-	-	-	-	-	-	-	-	-
BU100SW	120	120	60	35	20	15	7	5(700W)	-	-	-	-	-	-	-	-	-	-	-
BU100SW+BUM100S×1	720	420	240	120	80	60	40	30(700W)	-	-	-	-	-	-	-	-	-	-	-
BU150SW	210	150	70	37	23	17	10	7	4.2	4(1050W)	-	-	-	-	-	-	-	-	-
BU150SW+BUM150S×1	740	440	260	140	90	65	43	28	21	20(1050W)	-	-	-	-	-	-	-	-	-
BU75RW	250	150	85	36	23	18	10	-	-	-	-	-	-	-	-	-	-	-	-
BU75RW+BUM100R	860	520	320	170	100	75	44	-	-	-	-	-	-	-	-	-	-	-	-
BU100RW	250	150	85	36	23	18	10	7	-	-	-	-	-	-	-	-	-	-	-
BU100RW+BUM100R	860	520	320	170	100	75	44	31	-	-	-	-	-	-	-	-	-	-	-
BU200RW	320	220	150	80	52	40	26	18	14	11	9	7	-	-	-	-	-	-	-
BU200RW+BUM300R×1	900	800	500	240	200	150	100	75	55	44	35	30	-	-	-	-	-	-	-
BU300RW	320	220	150	80	52	40	26	18	14	11	9	7	6	5.3	4.3	4(2400W)	-	-	-
BU300RW+BUM300R×1	900	800	500	240	200	150	100	75	55	44	35	30	26	23	19	18(2400W)	-	-	-
BU60RE	115	75	42	19	12	8	6(480W)	-	-	-	-	-	-	-	-	-	-	-	-
BU100RE	150	110	72	32	20	15	8.5	6	-	-	-	-	-	-	-	-	-	-	-
BU100RE+BUM100RE×1	680	470	280	137	86	62	36	25	-	-	-	-	-	-	-	-	-	-	-
BU100RE+BUM100RE×2	1210	840	480	240	160	115	72	48	-	-	-	-	-	-	-	-	-	-	-
BU100RE+BUM100RE×3	1740	1190	720	370	250	178	110	75	-	-	-	-	-	-	-	-	-	-	-
BU1002SW	180	120	60	35	20	15	7	5(700W)	-	-	-	-	-	-	-	-	-	-	-
BU1002SW+BUM100S×1	720	420	240	120	80	60	40	30(700W)	-	-	-	-	-	-	-	-	-	-	-
BU3002SW	360	250	170	92	58	46	30	20	15	12	10	8	7	5.5	5(210W)	-	-	-	-
BU3002SW+BUM100S×1	1030	920	570	340	220	175	115	85	62	49	43	37	31	26	24(2100W)	-	-	-	-
BU1002RW	140	80	48	24	15	11	6	3.5	-	-	-	-	-	-	-	-	-	-	-
BU2002RWL	360	190	110	60	39	27	16	12	9.5	7	5	-	-	-	-	-	-	-	-
BU3002RWL	450	260	165	93	63	45	28	19	15	11	9	7.5	6	5.2	5(2100W)	-	-	-	-
BU5002RWL	660	480	320	200	140	106	68	50	39	31	25	21	18	16	15(2100W)	10	8	7	5

■后备时间的参考标准（停产机型）■

※周围温度为20℃、电池初始状态时。本后备时间表仅供参考。根据外部环境（温度等）不同，电池寿命也不同。

●后备式 时间单位：（分钟）

型号/负载容量	20W	50W	100W	200W	300W	400W	500W	700W	1000W	1400W
BZ35T (*1)	74	28	10	3	-	-	-	-	-	-
BZ50T (*1)	90	45	19	6	3	-	-	-	-	-
BZ50LT (*1)	90	45	19	6	3	-	-	-	-	-
BX50LS (*1)	90	50	20	6	3	-	-	-	-	-
BX25XT (*1)	40	22	8	3.5 (168W)	-	-	-	-	-	-
BX35XFV/BX35XFS (*1)	90	50	20	6	5 (210W)	-	-	-	-	-
BX50XFV/BX50XFS (*1)	90	50	20	6	3.5	-	-	-	-	-
BX75XS2 (*1)	90	90	50	22	12	7	5 (450W)	-	-	-
BU251X (*1)	70	30	10	5 (165W)	-	-	-	-	-	-
BU504X4/BU504XL4 (*2)	60	60	30	14	8	5	-	-	-	-
BU1004X3 (*2)	60	60	55	25	20	12	8	5	-	-

(\*1) 最大后备时间的限制。无法后备60分钟以上。

(\*2) 最大后备时间的限制。无法后备60分钟以上。

●在线互动式 时间单位：（分钟）

型号/负载容量	20W	50W	100W	200W	300W	400W	500W	700W	1000W	1400W
BN50XS	150	80	40	20	12	8 (335W)	-	-	-	-
BN75XS	150	80	40	20	12	7	5	-	-	-
BN100XS	240	120	60	35	21	15	11	5 (670W)	-	-
BN140XS	360	180	100	50	32	21	16	10	5 (940W)	-

●在线式 时间单位：（分钟）

型号/负载容量	20W	50W	100W	200W	300W	400W	500W	700W	1000W	1400W
BU50XS	120	75	40	20	12	8 (350W)	-	-	-	-
BU70XS	120	75	40	20	12	7	5 (490W)	-	-	-
BU100XS	180	120	60	35	20	15	10	5	-	-
BU100XS+MB100XSU	720	420	240	120	80	60	50	30	-	-
BU100XR2	180	120	60	35	20	15	10	5	-	-
BU100XR2+MB100XR2	720	420	240	120	80	60	50	30	-	-
BU200XR2	420	240	120	80	50	35	28	17	10	5
BU200XR2+MB200XR2x1	780	480	360	180	100	80	65	40	30	17
BU200XR2+MB200XR2x2	1320	900	420	270	180	120	100	70	50	32
BU606II	120	60	30	18	10	5 (420W)	-	-	-	-
BU1006II	180	80	50	23	18	10	8	5	-	-
BU1006II + MB1006 IIx1	300	180	100	55	33	28	23	14	-	-
BU2006II	---	150	100	70	50	40	28	20	14	5
BU2006II + MB2006II x1	480	300	210	150	100	80	70	50	30	20
BU2006II + MB2006II x2	720	600	360	210	150	120	100	70	60	33
BU606F	150	90	40	19	12	5 (420W)	-	-	-	-
BU1006F	180	90	60	25	18	12	9	5	-	-
BU1006F+MB1006Fx1	360	240	120	70	40	30	24	15	-	-
BU1006F+MB1006Fx2	720	360	240	100	70	55	37	25	-	-

型号/负载容量	20W	50W	100W	200W	300W	400W	600W	800W	1000W	1200W
BH60PCW (*3)	65	40	23	13	8	5.1	5 (420W)	-	-	-
BH100PCW (*3)	100	70	45	25	14	10	5	4 (700W)	-	-
BH100PCW+BHM100PCx1	210	140	95	50	35	25	15	12 (700W)	-	-
BH100PCW+BHM100PCx2	320	220	140	80	55	40	25	20 (700W)	-	-
BH100PCW+BHM100PCx3	430	300	190	110	75	55	35	30 (700W)	-	-
BH100PCW+BHM100PCx4	550	380	260	140	95	70	45	40 (700W)	-	-

(\*3) BH60PCW、BH100PCW共同为电池单元的标配，2个单元为基本构成。